

Duct Rods

A high quality fibre glass rod, specially constructed to provide exceptionally high tensile strengths, whilst retaining flexibility. The 80% fill rate glass fibre core is reinforced with a high strength resin. A braided reinforcing wrap is added

before the final polypropylene wear resistant protective coating is applied. The continuous rods range from 4.5mm (0.18") - 14mm (0.55") with lengths from 30 metres (98ft) - 300 metres (984ft).

| Product Code: | Length | Weight | Cassette Dimensions | | | Min. Bend Radius | Breaking Strength |
|-------------------------------|---------------|-----------------|---------------------|------------------|-----------------|------------------|-------------------|
| | | | Diameter mm (inch) | Height mm (inch) | Width mm (inch) | | |
| Mini Rod 4.5mm (0.18") | | | 400 (16") | 520 (20") | 162 (6.4") | 140 (5.5") | 770 (1700) |
| B-101-030 | 30m (98ft) | 4.5kg (9.9lbs) | | | | | |
| B-101-050 | 50m (164 ft) | 4.8kg (10.5lbs) | | | | | |
| B-101-060 | 60m (197 ft) | 5.0kg (11lbs) | | | | | |
| B-101-070 | 70m (229 ft) | 5.3kg (11.6lbs) | | | | | |
| B-101-080 | 80m (262 ft) | 5.5kg (12lbs) | | | | | |
| Midi Rod 6.7mm (0.26") | | | 600 (24") | 730 (29") | 210 (8") | 250 (10") | 2500 (5500) |
| B-102-060 | 60m (197 ft) | 9kg (19.8lbs) | | | | | |
| B-102-080 | 80m (262 ft) | 10kg (22lbs) | | | | | |
| B-102-100 | 100m (328 ft) | 11kg (24lbs) | | | | | |
| B-102-150 | 150m (492 ft) | 13kg (28lbs) | | | | | |
| Maxi Rod 9mm (0.35") | | | 850 (33") | 940 (37") | 520 (20") | 310 (12") | 3800 (8400) |
| B-103-060-800 | 60m (197 ft) | 29kg (63.8lbs) | | | | | |
| B-103-080-800 | 80m (262 ft) | 31kg (68lbs) | | | | | |
| B-103-100-800 | 100m (328 ft) | 33kg (72lbs) | | | | | |
| B-103-120-800 | 120m (393 ft) | 35kg (77lbs) | | | | | |
| B-103-150-800 | 150m (492 ft) | 38kg (83lbs) | | | | | |
| Maxi Rod 11mm (0.43") | | | 1110 (43") | 1130 (44") | 520 (20") | 390 (15") | 6000 (13200) |
| B-104-100-1000 | 100m (328 ft) | 42kg (92lbs) | | | | | |
| B-104-150-1000 | 150m (492 ft) | 48kg (105lbs) | | | | | |
| B-104-200-1000 | 200m (656 ft) | 55kg (121 lbs) | | | | | |
| B-104-250-1000 | 250m (820 ft) | 62kg (136 lbs) | | | | | |
| B-104-300-1000 | 300m (984 ft) | 69kg (152 lbs) | | | | | |
| Maxi Rod 14mm (0.55") | | | 1300 (51") | 1300 (51") | 550 (21") | 500 (20") | 9000 (19800) |
| B-105-150-1200 | 150m (492 ft) | 70kg (154 lbs) | | | | | |
| B-105-200-1200 | 200m (656 ft) | 84kg (186 lbs) | | | | | |
| B-105-250-1200 | 250m (820 ft) | 98kg (217 lbs) | | | | | |
| B-105-300-1200 | 300m (984 ft) | 113kg (249 lbs) | | | | | |

Spare rod is available for all models.
For example: B-101-020-01 Spare Rod 30m.

Rod Specification

Core Rod: E-Glass+Vinylester
Coating: Polypropylene, UV Stabilised

